

Bartoline all purpose wallpaper adhesive 200G

Bartoline All Purpose Wallpaper Adhesive is a traditional, high quality, easy to mix flake adhesive. It is easily spread with excellent slip properties for accurate positioning and longlasting results. Suitable for hanging all wallpaper types.

Directions

Preparation: Ensure surface is clean, dry and free from dust. Treat areas where there is a high risk of mould growth with Bartoline Fungicidal Wash. Size absorbent surfaces before use and allow to dry completely before papering.

Mixing: Add the correct volume of cold water to a clean bucket based on the mix ratio table. Sprinkle the contents of the sachet into the water and stir briskly for 30 seconds to evenly mix. Leave to stand for 3 minutes then stir again thoroughly. The paste is now ready to use.

Pasting: Follow the wallpaper manufacturer's instructions. Soak heavy and embossed paper until supple. Paste generously, particularly the edges, and do not overspread. Take care to avoid getting adhesive on the patterned side of the paper, removing any splashes with a damp sponge. When applying paste the wall wallpapers apply paste directly onto the surface to be papered.

Mix Ratio Tables

APPLICATION	Quantity of cold water to use per sachet	Approximate coverage per sachet*
Normal wallpapers including woodchip	12 Pints / 7 Litres	8 - 10 Rolls
Vinyl wallcoverings, washables and Novamura	10 Pints / 5.7 Litres	8 Rolls
Blown vinyl wallcoverings	10 Pints / 5.7 Litres	8 Rolls
Embossed papers (e.g. Anaglypta)	8 Pints / 4.5 Litres	4 - 5 Rolls
Heavy embossed papers (e.g. Supaglypta)	7 Pints / 4 Litres	3 - 4 Rolls
Paste the walls	8 Pints / 4.5 Litres	2 - 4 Rolls
Polystyrene tiles	8 Pints / 4.5 Litres	48 m ²
*NB: These figures are intended as a guide only. SIZING: When sizing walls before papering, mix contents of sachet into 16 pints (9 Litres) of cold water.		

Health and Safety

See MSDS for full information

Measurement	Value	Test Method
Physical State	Fine Scalings	Visual
Colour	Off White	Visual
Odour	Wallpaper paste	
Flash point	Not Applicable	
VOC content	None	

Customs Tariff Code

3505 1050

Shipping Classification

Non-Hazardous for shipping purposes